

Engine

Engine Model	KM385 Engine
Engine Gross Power	25 hp (18.4KW)
Rated Speed	2350 rpm
No. of Cylinders	3 Cylinders
Fuel Type	Diesel
Aspiration	Natural
Displacement	1530cc
Fuel Tank Capacity	21 litres
Pre Heating System	Glow Plugs

Transmission

Transmission	Manual
No. of Travel Speed Forward/Reverse	8 Forward 8 Reverse

Power Take off

P.T.O. Type	Dual Speed, Semi Independent
P.T.O. Power	16.5 KW
P.T.O. Speed	540/1000rpm

Brakes and Clutch

Brakes	Dry disc
Clutch	Dry, dual stage

Dimensions w/Ag tyres 4WD

Wheelbase	1690mm
Front Tread	1215mm
Rear Tread	1100 ~ 1350mm
Ground Clearance	347mm
Turning Radius w/Brake	2600mm
Turning Radius wo/Brake	3100mm

Hydraulics

Total Pump Flow	27 litres/minute
Max. Hydraulic Working Pressure	18.5 Mpa
No. of Spool Valves	5

3 Point Linkage

Standard Category	Cat. 1
Lift Capacity	4.1 Kn
Control Type	Position

Weight 4WD

Weight with Ag Tyres w/ROPS	1230 kg
-----------------------------	---------

Tyres

Ag 4WD Front	6 - 14
Ag 4WD Rear	9.5 - 24

Standard Equipment

Shuttle Shift
Foldable ROPS and Sun Shade (90 and 45 degree positions)
PTO Guard
Swinging Draw Bar
Rear PTO
Dry Dual Clutch
Rear Differential Lock
3 Point Hitch with multiple position stabiliser
Comfortable, adjustable sprung seat with seat belt
Front Weights with Tow Hitch
Lockable Tool Box
Hydraulic Spool Outlets for Hydraulic Implement Control
Hydrostatic Power Steering
Hand and Foot operated throttle
Road head lights and rear ploughing light
Manual Engine Stop Knob
Selectable 4WD
Diff Lock
Hour meter

Instrument Panel

Coolant Temperature Gauge
Electrical Tachometer
Fuel Gauge
Engine Oil Pressure Warning Light
High Beam, Indicator, Hazard Warning Lights
Glow Plug Light
Battery Charging Warning Light

Euroleopard (25hp) 4wd

At home in gardens, paddocks and equestrian yards alike; the 2500 series is compact, agile and versatile with the advantage of 4 wheel drive, the 2500 series is the perfect size for the smallest of tasks, whilst having enough power to tackle any job that demands a durable, compact tractor.

Standard Features

Direct Injection Diesel Engine

The 25hp Perkin's technology direct injection diesel engine boasts both reliability and environmental friendliness. It supplies a large output and offers low fuel consumption.

8 x 8 Shuttle Transmission

The shuttle transmission allows a diverse range of high and low range gearing to meet different working requirements for easier FEL operation.

Selectable 4 Wheel Drive

4 Wheel Drive can be easily selectable by a conveniently located lever.

Twin Speed PTO (540/1000rpm)

The twin speed PTO allows the tractor to operate at either 540 or 1000 rpm to meet every implement requirement.

3 Point Linkage

With an adjustable 3 point linkage complete with multiple position stabilisers, the attachment of implements is made easy.

Power Steering

Make easy work of maneuvering the tractor with power steering.

Twin Live Drive Clutch

With the twin position live drive clutch, both the drive and the PTO transmissions are quickly and easily selectable.

5 Hydraulic Spool Valves

The rear mounted spool valves allow the fitting of a choice of implements and attachments - from tipping trailers to back hoes.

Roll Over Protection System

Australian Certified folding roll over protection system for essential safety. Comfortable seat and seatbelt also fitted as standard.

Choice of Agricultural or Turf Tyres

Choose between agricultural or turf tyres depending on your intended usage.

European Vehicle Type Approval

Conformation that Foton Tractors meet European Performance and Safety standards. EC Directive 2003/37/EC



2500 SERIES

XTREME MACHINERY

4 Cullen Street, Bayswater WA 6053. T. 08 9471 9788 F. 08 9471 9780.
E. xtrememoto@bigpond.com Website: www.xtrememachinery.com.au
Chris M 0439978811 Geoff M 0439978877 Brett M0417962972

